

# ALL-IN-ONE AIR THAT WON'T QUIT

Tank-mounted industrial air compressors give you serious air power in a compact, plug-and-play package. You get reliable, clean air, lower energy costs and less downtime – so your shop can stay focused on turning out work, not chasing air problems.

### ALL-IN-ONE, SPACE-SAVING DESIGN

Compressor, 120-gallon tank and optional dryer come together in a compact footprint, freeing up floor space while delivering clean, dry air from a single, ready-to-work package.

### BUILT FOR RELENTLESS UPTIME

High-efficiency IE3 motor, IP55 protection and a durable airend are engineered for continuous duty, so your shop can run day, night and weekends without worrying about your air supply.

### LOWER ENERGY, LOWER OPERATING COSTS

Optimized rotor profiles and efficient components cut internal losses and reduce the torque required, delivering energy savings to help trim your power bill.

### PLUG-AND-PLAY INSTALLATION

A tri-voltage, pre-wired package connects to common 208V, 230V or 460V three-phase power – no special transformers, no extra hassle. Hook it up and get to work fast.

### VERSATILE PRESSURE FOR MANY JOBS

Wide operating range with a simple pulley kit conversion from 100 to 175 psi lets one machine handle everything from pneumatic tools and paint spraying to higher-pressure applications like plasma cutting or nitrogen generation.

### SCALE UP EASILY

If your shop needs more flow down the road, you can connect another unit and use controllers to efficiently manage the bigger load.

### EASY, FAST MAINTENANCE

Large access panels, spin-on filters, clear sight glasses and centralized drains make routine service quick and clean, helping you cut downtime and keep operations moving.

### CLEAN, DRY AIR

Advanced air-oil separation, multi-stage filtration, oversized aftercooler and optional dryer help keep oil, dust and moisture out of your airlines, delivering clean, dry air to your application.

### CONFIDENCE YOU CAN COUNT ON

Robust safeguards, reliable components and a five-year bumper-to-bumper warranty give you the confidence to push your schedule hard, knowing your air compressor system is built to keep up.



| Model                           | Pressure           | Capacity*        | Pressure Conversion Kit Part No. | Motor Power    | Length           | Width           | Height           | Weight            |
|---------------------------------|--------------------|------------------|----------------------------------|----------------|------------------|-----------------|------------------|-------------------|
| <b>SA10TD</b><br>(With Dryer)   | 100 psi (689 kPa)  | 44 cfm (1.2 cmm) | 46956385                         | 10 hp (7.5 kW) | 81 in. (2057 mm) | 28 in. (711 mm) | 62 in. (1574 mm) | 1098 lb. (498 kg) |
|                                 | 125 psi (861 kPa)  | 39 cfm (1.1 cmm) | 46956386                         |                |                  |                 |                  |                   |
|                                 | 150 psi (1034 kPa) | 34 cfm (0.9 cmm) | 46956387                         |                |                  |                 |                  |                   |
|                                 | 175 psi (1206 kPa) | 28 cfm (0.7 cmm) | 46956388                         |                |                  |                 |                  |                   |
| <b>SA10T</b><br>(Without Dryer) | 100 psi (689 kPa)  | 44 cfm (1.2 cmm) | 46956385                         | 10 hp (7.5 kW) | 80 in. (2032 mm) | 28 in. (711 mm) | 57 in. (1447 mm) | 975 lb. (442 kg)  |
|                                 | 125 psi (861 kPa)  | 39 cfm (1.1 cmm) | 46956386                         |                |                  |                 |                  |                   |
|                                 | 150 psi (1034 kPa) | 34 cfm (0.9 cmm) | 46956387                         |                |                  |                 |                  |                   |
|                                 | 175 psi (1206 kPa) | 28 cfm (0.7 cmm) | 46956388                         |                |                  |                 |                  |                   |
| <b>SA15TD</b><br>(With Dryer)   | 100 psi (689 kPa)  | 68 cfm (1.9 cmm) | 46955957                         | 15 hp (11 kW)  | 80 in. (2032 mm) | 28 in. (711 mm) | 65 in. (1651 mm) | 1268 lb. (575 kg) |
|                                 | 125 psi (861 kPa)  | 63 cfm (1.7 cmm) | 46955958                         |                |                  |                 |                  |                   |
|                                 | 150 psi (1034 kPa) | 55 cfm (1.5 cmm) | 46955959                         |                |                  |                 |                  |                   |
|                                 | 175 psi (1206 kPa) | 51 cfm (1.4 cmm) | 46955960                         |                |                  |                 |                  |                   |
| <b>SA15T</b><br>(Without Dryer) | 100 psi (689 kPa)  | 68 cfm (1.9 cmm) | 46955957                         | 15 hp (11 kW)  | 80 in. (2032 mm) | 28 in. (711 mm) | 61 in. (1549 mm) | 1140 lb. (517 kg) |
|                                 | 125 psi (861 kPa)  | 63 cfm (1.7 cmm) | 46955958                         |                |                  |                 |                  |                   |
|                                 | 150 psi (1034 kPa) | 55 cfm (1.5 cmm) | 46955959                         |                |                  |                 |                  |                   |
|                                 | 175 psi (1206 kPa) | 51 cfm (1.4 cmm) | 46955960                         |                |                  |                 |                  |                   |
| <b>SA20TD</b><br>(With Dryer)   | 100 psi (689 kPa)  | 81 cfm (2.2 cmm) | 46956486                         | 20 hp (15 kW)  | 80 in. (2032 mm) | 28 in. (711 mm) | 65 in. (1651 mm) | 1283 lb. (582 kg) |
|                                 | 125 psi (861 kPa)  | 79 cfm (2.2 cmm) | 46956487                         |                |                  |                 |                  |                   |
|                                 | 150 psi (1034 kPa) | 75 cfm (2.1 cmm) | 46956488                         |                |                  |                 |                  |                   |
|                                 | 175 psi (1206 kPa) | 68 cfm (1.9 cmm) | 46956489                         |                |                  |                 |                  |                   |
| <b>SA20T</b><br>(Without Dryer) | 100 psi (689 kPa)  | 81 cfm (2.2 cmm) | 46956486                         | 20 hp (15 kW)  | 80 in. (2032 mm) | 28 in. (711 mm) | 61 in. (1549 mm) | 1212 lb. (549 kg) |
|                                 | 125 psi (861 kPa)  | 79 cfm (2.2 cmm) | 46956487                         |                |                  |                 |                  |                   |
|                                 | 150 psi (1034 kPa) | 75 cfm (2.1 cmm) | 46956488                         |                |                  |                 |                  |                   |
|                                 | 175 psi (1206 kPa) | 68 cfm (1.9 cmm) | 46956489                         |                |                  |                 |                  |                   |

\*Unit performance measured according to ISO 1217, Annex C, latest edition.